

# SEISMIC SERIES FRAME FS84EQ-3 W/CAGE-NUT RAILS

## DIMENSIONS


### FRAME SEISMIC

2x2 TUBING (16GA)  
GUSSETS FOR FLOOR AND REAR BRACING  
(19" RACKABLE PER E.I.A STD)  
FOUR POINT ADJUSTABLE LEVELING  
HEIGHT 84.00"  
WIDTH 24.00"  
DEPTH 42.00"


## RAIL TYPE

### L-TYPE RAILS


CAGE-NUT, M6 SCREWS  
FULLY ADJUSTABLE FRONT TO REAR  
45U




TOP VIEW



FRONT VIEW



SIDE VIEW



ALL INFORMATION ARE PROPRIETARY DATA OF DAMAC PRODUCTS INC. ANY REPRODUCTION/USE IN ANY FORM MUST HAVE PRIOR WRITING AGREEMENT W/ DAMAC.  
TOLERANCE .00X±.010 .00X±.030 .X±.080 (DEG)±.5  
ALL DIM. ARE IN INCHES UNLESS OTHERWISE SPECIFIED

TITLE: FRAME, SEISMIC  
84" x 24" x 42"  
NEBS RATED

PART NO. FS84EQ-3  
DRAWN BY: AP DATE: 07.20.2006

CHECKED BY: CR  
SHEET: 1 OF 1

SCALE: N/A  
MATERIAL: N/A  
FINISH: BLACK POWDER-COATED  
MAX BEND R=.030, RELIEF=.060 A/R.  
UNLESS OTHERWISE SPECIFIED